

# Efcon® Wall-mounted / Portable Sampler



Sampler for wall mounting with sturdy thermoplastic housing.

Easy to transport - ideal for use as portable sampler together with the separately available rack

The economic solution when no temperature-controlled cabinet for the samples is needed or if sampling is only required temporary.

The modern controller Jazz with LCD display allows time, flow and event proportional sampling.

**ISO 5667**

- Easy to transport
- Lightweight
- Patented, sturdy housing with 2 years warranty
- Modern controller

## Method

The Efcon® wall-mounted sampler employs the established vacuum sampling method. On request available with peristaltic pump.

Sample container: collective sample

## Applications

Wastewater, including industrial wastewater

## Technical data

### **Efcon® wall/portable**

Sample container	Collective sample 20 L
Main switch	No
Ambient temperature	0~40 °C
Zone	Not for use in areas of explosion hazard
Housing	Fibre-reinforced LLDPE
Protection class	IP 54
Dimensions	340 mm × 412 mm × 302 mm ± 2%
Weight	9 kg (empty)
Power supply	230 V AC ± 5%, 50 Hz

### **With vacuum sampling**

Required conductivity	50 µS
Suction height	4 m, optional 6 m, on request up to 12 m

**Efcon® wall-mounted**  
**For portable sampling**

**product code 774 270**  
**product code 774 272**